

Tapered Roofing




Molded Polystyrene Insulation.

Foam-Control® tapered roofing insulation is a cost-effective, durable and energy efficient solution for roof insulation. Foam-Control tapered roofing insulation provides the positive drainage necessary for commercial roofing systems. Foam-Control insulation is compatible with all major roofing materials and assemblies.

- Cost effective roof insulation
- R-value that never changes and is stable over time
- Range of compressive strength available
- Provides economical one-step tapered roof system
- Custom crickets and saddles are fast to install

Sample Tapered Cross Section.



Foam-Control is available in a wide range of R-values and thicknesses to meet your needs. Product thicknesses are provided in the Foam-Control Thickness Selector. Project requirements vary, so Foam-Control can be ordered in any R-value thicknesses to meet your needs.

Proven to meet, or exceed, building codes.

Foam-Control is manufactured under an industry leading quality control program monitored by UL and further recognized in UL Evaluation Report UL ER11812-01. Foam-Control meets ASTM C578, "Standard Specification for Rigid, Cellular Polystyrene Thermal Insulation".



Sizes.

Foam-Control tapered insulation is available in 4' x 4' and 4' x 8' panels with thickness from 1/2" to 24" in a single layer. There are no limitations to available slope per foot.


Crickets and Saddles.

Foam-Control tapered insulation is also available in factory cut cricket and saddle configurations.

FOAM FACTS:

Foam-Control outperforms XPS.

- Foam-Control provides a stable long-term R-value at a lower cost
- Foam-Control uses a blowing agent with 10 x lower global warming potential and 10,000 x lower ozone depletion
- Foam-Control meets strength requirements at a lower cost
- Foam-Control and XPS have resistance to moisture, but Foam-Control has a higher vapor permeance leading to superior drying potential



Performance Value.

When you consider all performance characteristics and cost, Foam-Control is your best choice for foam insulation.

Foam-Control has air in its closed cells and therefore has a stable R-value. Many other insulations use blowing agents that cause R-value loss and are harmful to the environment.

Foam-Control has compressive strength to meet specific project requirements.

Foam-Control is manufactured to resist moisture absorption in wetting conditions and release absorbed moisture quickly during drying periods, which means Foam-Control maintains R-value.

Termite Resistant - Perform Guard®.

One of the most destructive forces anywhere is termites. Foam-Control can be manufactured with Perform Guard, a proven and safe additive, that effectively resists termites.

Foam-Control with Perform Guard meets ICC ES AC239, "Acceptance Criteria for Termite-Resistant Foam Plastics".

Recyclable.

After its life as a building insulation, Foam-Control is 100% recyclable. It can be ground into granules and reincorporated into new Foam-Control products or it can be thermally processed into a resin that's used to manufacture other new products.

Ready to take control? Start here.

If you're ready to have Foam-Control contribute to your next project, just contact your nearest Foam-Control manufacturer and Technical Sales Representative. They will be happy to give you design consultation, information about Foam-Control products, pricing, and answers to all of your questions.



BIG SKY INSULATIONS, INC
 15 Arden Drive | P.O. Box 838
 Belgrade, MT 59714

Email: answers@bigskycontrol.com
 Website: www.bigskyfoamcontrol.com



Foam-Control products are manufactured by AFM Corporation licensees.

Copyright © 2020 AFM Corporation. All rights reserved. Printed in USA. Foam-Control and the Foam-Control logo are registered trademarks of AFM Corporation, Lakeville, MN.

UL logo is a registered trademark of UL LLC. USGBC logo is a registered trademark of U.S. Green Building Council.

R012-01/20



www.foam-control.com

**MOLDED
 POLYSTYRENE
 INSULATION**